



# REXNORD BEARING LIMITED

2.75 Inch | 69.85 Millimeter x 4 Inch | 101.6  
Millimeter x 3.25 Inch | 82.55 Millimeter  
REXNORD ZAS221272 Pillow Block Bearings



Bearing No. ZAS221272

ZAS221272 Bearing 2D drawings and 3D CAD models

|                           |  |
|---------------------------|--|
| Category                  | Pillow Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 13.529   |
| EAN                       | 0698210830564  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 2212U  |
| Seals                     | Clearance Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch - Metric             | Inch   |
| Other Features            | Double Row   Normal Duty<br>  Single Collar   With Set<br>Screw  |
| Long Description          | 2 Bolt Pillow Block; 2-3/4"<br>Bore; 3-1/4" Base to Center<br>Height; Concentric Collar<br>Mount; Spherical Roller |



## REXNORD BEARING LIMITED

|                               |  |
|-------------------------------|--|
|                               | Bearing; Relubricatable;<br>Cast Steel; Clearance Seal;<br>Expansion |
| Category                      | Pillow Block   |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer URL              | <a href="http://www.rexnord.com">http://www.rexnord.com</a>          |
| Manufacturer Item Number      | ZAS221272  |
| Manufacturer Internal Number  | 6883056  |
| Weight / LBS                  | 25.5   |
| d                             | 2.75 Inch   69.85 Millimeter   |
| Actual Bolt Center to Center  | 8.1 Inch   206 Millimeter  |
| Nominal Bolt Center to Center | 8.1 Inch   206.4 Millimeter  |
| Bolt Spacing Maximum          | 0 Inch   0 Millimeter  |
| D                             | 4 Inch   101.6 Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0 Millimeter  |
| B                             | 3.25 Inch   82.55 Millimeter   |